

Model: WR6500H

BE6500

2.5G Wi-Fi 7 Router









Supercharged Speed. Blazing-Fast Wi-Fi.

For the first time, MLO in Wi-Fi 7 connects clients through multiple bands simultaneously, aggregating the speed and making congestion on any single band insensible. In addition, the 4K-QAM boosts speed by another 20%, delivering a total of 2.7X faster speed for smoother experience in larger homes.



Versatile Management



Parental Control

Set up profiles with corresponding policies to establish a safer network for your loved ones.



IPv6

Support the IPv6 services by your ISP and browse the IPv6 websites with faster performance.



VPN Client and Server

Cudy APP Control

remote management.

Connect and share a VPN or establish your own server to secure remote access.

Manage your network right on your

phone. This device supports cloud



IP1

Includes Tag VLAN to support assigning IPTV/VoIP ports. IGMP snooping improves IPTV network efficiency.



→ QoS

Set speed limits for certain clients to prioritize your gaming rigs and other important devices.

Immersive Gaming with Lower Latency

The enhanced OFDMA with multi-RU and puncturing utlize non-busy frequency resource unit to fit more connections at the same time.



Powerful Wi-Fi 7 Chip for Responsive Network

The next-gen Wi-Fi 7 Broadcom CPU with fabulous efficiency processes more tasks instantly, keeping network super-capable and responsive.





Highlights

A dual-band WiFi 7 router with an aggregate of 6.5 Gbps speed, and five Gigabit ports, catering to super-fast internet access, gaming, and entertainment scenarios.

- Broadcom 2 GHz Quad-Core CPU
- 6-Stream Dual-Band Wi-Fi 7
- 5760 Mbps + 688 Mbps Wi-Fi
- 1× 2.5GbE and 4× GbE
- 200 Connected Devices
- Covers 140 m² (1,500 ft²)
- Cudy Mesh, VPN Server and Client
- Cudy App, Cloud Control

Package Content

- WR6500H
- Power Adapter
- Ethernet Cable
- Installation Guide

Hardware Specs

| CPU | Chipset | BCM6766 | |
|----------------|--------------------------|---|--|
| | CPU Details | 2.0 GHz Quad-core, ARM Cortex-A7 | |
| Memory/Storage | Flash/ROM | 128 MB (1 Gbit) NAND | |
| | DDR/RAM | 512 MB (4 Gbit) DDR4 | |
| Wireless | 5 GHz Wi-Fi Speed | 5765 Mbps | |
| | 2.4 GHz Wi-Fi Speed | 688 Mbps | |
| | 5 GHz Wi-Fi Streams | 4T4R (4×4 MIMO) | |
| | 2.4 GHz Wi-Fi Streams | 2T2R (2×2 MIMO) | |
| | Wi-Fi Antennas | 6× Fixed | |
| | 5 GHz Antenna Gain Max | 5.27dBi | |
| | 2.4 GHz Antenna Gain Max | 5.19dBi | |
| | FEM or PA/LNA | 5 GHz: 4× External | |
| | | 2.4 GHz: 2× External | |
| | Beamforming | True | |
| | Range Performance | Max: 240 m (787 ft) | |
| | | Indoor WiFi range varies depending on the | |
| | | layout and wall materials. See Wall | |
| | | Performance spec for placement suggestions | |
| | Wall Performance | Two wooden walls with thickness < 10 cm (4") | |
| | | One concrete wall with thickness < 20 cm (7") | |
| | | or two concrete walls with thickness < 10 cm (4") | |



Hardware Specs

| Interfaces | 2.5G RJ45 Ports | 1 |
|------------|---------------------------|---------------------------------|
| | Gigabit RJ45 Ports | 4 |
| | Ethernet Notes | The 2.5G port is WAN port, |
| | | the Gigabit ports are LAN ports |
| | LED | System |
| | | Internet |
| | | Wi-Fi |
| | | WPS |
| | Physical Buttons | Power On/Off Button |
| | | WPS Button |
| | | Reset Button |
| Power | Power Input | DC Jack |
| | Power Methods | DC |
| | DC | 12V 1.5A |
| | Power Adapter | Input: 100 ~ 240 V, 50/60 Hz AC |
| | | Output: 12V 1.5A DC |
| | Max Power Consumption (W) | 17W |
| | | |

| Reliability | Environment | Operating Temperature: |
|----------------------|--------------------------|---|
| | | 0 °C ~ 40 °C (32 °F ~104 °F) |
| | | Storage Temperature: |
| | | -40 °C ~ 70 °C (-40 °F ~ 158 °F) |
| | | Humidity: 10% ~ 90% non-condensing |
| | | Storage Humidity: 5% ~ 95% non-condensing |
| Certifications | FCC, CE | |
| Mechanical | Installation | Desktop |
| | | Wall-mount |
| | Dimension | 253×152.5×48.2 mm |
| | | 9.96×6×1.9 inches |
| | Product Weight | 580.0 g (20.46 oz.) |
| Ordering Information | Retail Package Weight | EU: 1190.0 g (41.98 oz.) |
| | Retail Package Dimension | 431×324×58 mm |
| | | 16.97×12.76×2.28 inches |
| | Units per Carton | 8 |
| | Carton Dimension | 49.2×44.5×34.4 cm |
| | | 19.37×17.52×13.54 inches |
| | Carton Gross Weight | EU: 10.5 kg (23.15 lbs) |
| | Carton Net Weight | EU: 9.5 kg (20.94 lbs) |



Software Specs

| Wireless | Wi-Fi Standards | Wi-Fi 7 |
|----------|--------------------------------|----------------|
| | Max Wi-Fi Modulation | 4K-QAM |
| | Wi-Fi Efficiency | MLO |
| | | MRU |
| | | Puncturing |
| | | OFDMA |
| | | MU-MIMO |
| | | BSS Color |
| | Max Capacity | 512 |
| | Recommended Client Upper Limit | 200 |
| | Max Wi-Fi Channel Width | 160 MHz |
| | Wi-Fi Security | WPA/WPA2/WPA3 |
| | Guest Network | 2.4 GHz, 5 GHz |
| | WPS | True |
| General | Operation Modes | Wi-Fi Router |
| | | Access Point |
| | Multi-Band Backhaul | True |
| | WAN Mode | DHCP |
| | | Static IP |
| | | PPPOE |
| | | PPTP |
| | | L2TP |

| Network | QoS | Per-User Rate Limiting | |
|---------|-------------------|------------------------|--|
| | DHCP | Address Reservation | |
| | | DHCP Client List | |
| | | Server | |
| | IP Versions | IPv4/IPv6 | |
| | IPv6 Protocols | Relay | |
| | | Dynamic (SLAAC/DHCPv6) | |
| | | Static (Fixed IP) | |
| | | Passthrough | |
| | | 464XLAT | |
| | | MAP-E | |
| | | DS-Lite | |
| | IPTV/VLAN | Bridge | |
| | | Tag VLAN | |
| | | VoIP VLAN | |
| | | IPTV VLAN | |
| | TTL Customization | Extend | |
| | | Spoof | |
| | | Custom | |
| | IGMP | IGMP Proxy | |
| | | IGMP Snooping | |



Software Specs

| Network | Forwarding | Port Forwarding |
|-----------|---------------------------|-------------------|
| | | Port Triggering |
| | | UPnP |
| | | DMZ |
| | Firewall | SPI Firewall |
| | | DoS Protection |
| | | Block PING |
| | Application Layer Gateway | IPSec Passthrough |
| | | L2TP Passthrough |
| | | PPTP Passthrough |
| | | FTP Passthrough |
| | | TFTP Passthrough |
| | | H323 Passthrough |
| | | SIP Passthrough |
| | | RTSP Passthrough |
| Utilities | VPN Server | WireGuard |
| | | OpenVPN |
| | | IPsec |
| | | Zerotier |
| | | PPTP |
| | | L2TP |

| Utilities | VPN Client | WireGuard |
|------------|------------------------|-----------------------|
| | | OpenVPN |
| | | IPsec |
| | | Zerotier |
| | | PPTP |
| | | L2TP |
| | DNS Options | DNS over TLS |
| | | Manual DNS |
| | | Rebind Protection |
| | | Override Clients' DNS |
| | DNS over TLS Providers | Cloudflare |
| | | Google |
| | | Quad9 |
| | | Custom |
| | Wake on LAN | True |
| | Online Detection | True |
| Management | All Devices Management | Wi-Fi Time Schedule |
| | | MAC Filter |
| | | IP/MAC Binding |
| | Per-Devices Management | Internet On/Off |
| | | VPN On/Off |
| | | Online Time Schedule |
| | | Device Rename |



Software Specs

| System | LED Control | True |
|--------|-----------------------|---|
| | Local Control Method | Config Web Page |
| | | App Control |
| | Remote Control Method | Config Page via HTTPS |
| | | App Control |
| | | TR069/TR098/TR111/TR181 |
| | Firmware Upgrade | Local Update |
| | | App (Over the Air) |
| | | Online Update |
| | Reliability | Timed Reboot |
| | | Backup and Restore |
| | Diagnostic Tools | Diagnosis |
| | | Ping |
| | | Traceroute |
| | | NSLookup |
| | | System Log |
| | Languages | • English • Bengali • Catalan • Czech |
| | | • German • Greek • Spanish • French |
| | | • Hebrew • Italian • Croatian • Hungarian |
| | | • Khmer • Korean • Dutch • Japanese |
| | | • Russian • Slovak • Swedish • Romanian |

| System | Languages | • Turkish • Vietnamese • Thai • Ukrainian |
|-----------|-----------|--|
| | | • Polish • Norwegian • Portuguese |
| | | • Simplified Chinese • Traditional Chinese |
| Dashboard | Panel | Internet Status |
| | | Devices Management |
| | | WAN Status |
| | | LAN Status |
| | | Wi-Fi Status |
| | | VPN Status |
| | | DHCP Server Status |
| | | System Version |
| | Charts | Internet Speed |
| | | Wi-Fi Speed |