

# 3 Meters 10G SFP+ Direct Attach Cable

MODEL: SM5220-3M

## Features

- 10G SFP+ connector on both sides.
- Drives 10 Gigabit Ethernet (3m distance)

With a passive twin-ax cable assembly of 3 meters and two SFP+ connectors on each side, SM5220-3M (TL-SM5220-3M) is suitable for short distances and offers a cost-effective way to connect within racks and across adjacent racks.



## Specifications

Product Dimensions	<ul style="list-style-type: none"><li>• Plug: 2.26*0.53*0.34 in (57.5*13.55*8.55 mm)</li><li>• Overall length: 118.11 in (3,000 mm)</li></ul>
Cable Length	3 m
Data Rate	10 Gbps
Environment	<ul style="list-style-type: none"><li>• Operating Temperature: 0–70 °C (32–158 °F)</li><li>• Storage Temperature: -40–80 °C (-40–176 °F)</li><li>• Operating Humidity: 10–90% RH non-condensing</li><li>• Storage Humidity: 5–90% RH non-condensing</li></ul>
Conductor	Silver Plated Copper

[www.tp-link.com](http://www.tp-link.com)

Specifications are subject to change without notice. All brands and product names are trademarks or registered trademarks of their respective holders. © 2024 TP-Link