

Product:

UA-G3

Overview

Dimensions	93 x 40 x 36.5 mm (3.7 x 1.6 x 1.4")
NFC Card & Keyfob Access	✓
Apple/Google Wallet	✓
Mobile Unlock	✓
Handwave Request to Exit	✓
NDAA Compliant	✓
UL 294 Level	Destructive attack: Level I Line security: Level I Endurance: Level I Standby power: Level I
Weatherproofing	IP55

Mechanical

Weight	82 g (2.9 oz)
Enclosure Material	Polycarbonate, glass
Mount Material	Aluminum alloy
Mounting	In-wall, gang box (Included) Junction box (Optional)

Hardware

Indoor and Outdoor Use	Yes
Ambient Operating Temperature	-30 to 45° C



	(-22 to 113° F)
Ambient Operating Humidity	5 to 90% noncondensing
Networking Interface	(1) 10/100 MbE RJ45 port
Connectivity	BLE 4.1 NFC
Power Method	PoE UL 294 Power-limited Class 2 PSU UL 60950-1/62368-1 LPS/PS2 PSU
Max. Power Consumption	5W
Supported Voltage Range	48V DC
ESD/EMP Protection	Air: ±15kV, contact: ±8kV
Sensors	Proximity sensor
Speaker	✓
LEDs	R/G/B/W Learn More
Button	(1) Factory-reset
NFC Frequency	13.56 MHz
NFC Read Range	< 30 mm (1.18")
NFC Technology	ISO/IEC 14443A / 14443B / 15693 / 18092 (Ecma 340) MIFARE Classic / MIFARE DESFIRE Sony FeliCa™ (ID only) NFC Forum tags T1T, T2T, T3T, T4T and T5T ECP 2.0
PoE Cabling Requirements	Cat 5e cabling is the minimum performance category recommended. The performance category utilized should match the transmission speed required at the installation site. The minimal conductor gauge permitted to connect between the PSE or power injector and the PD shall be 26 AWG (0.13 mm ²) for



patch cords; 24 AWG (0.21 mm²) for horizontal or riser cable.

UL 294 Statement Compliance with IEEE 802.3 specifications was not verified as part of UL 294.

The equipment is intended to comply with the section of the National Electrical Code, ANSI/NFPA 70, Article 725.121, Power Sources for Class 2 and Class 3 Circuits.

CAN/ULC-60839-11-1 Grade Grade assignment: I

Certifications CE, FCC, IC, UL 294, CAN/ULC-60839-11-1

Document number, and issue date and/or revision level UA-G3, V01

Software

Management Application Access

Software Information The software version can be checked at <https://unifi.ui.com>





