

LTU Lite



Mechanical

| | |
|--------------------|--|
| Dimensions | 153 x 84 x 39.5 mm (6.02 x 3.31 x 1.56") |
| Weight | 250 g (8.82 oz) |
| Enclosure material | Outdoor UV-stabilized polycarbonate |
| Mount material | Polycarbonate |
| Mounting | Pole mount, wall mount (Kit included) |
| Wind loading | 20 N at 200 km/h (4.5 lbf at 125 mph) |
| Wind survivability | 200 km/h (125 mph) |

Hardware

| | |
|-------------------------|---|
| Networking interface | (1) GbE RJ45 port |
| Power method | 24V Passive PoE (Pairs 4, 5+; 7, 8-) |
| Power supply | 24, 0.5A Gigabit PoE adapter (Included) |
| Supported voltage range | 22–26V DC |
| Max. power consumption | 8.5W |
| ESD/EMP protection | Air/contact: ± 24 kV |
| RF connections | Internal |
| Button | Factory reset |
| Operating temperature | -40 to 55° C (-40 to 131° F) |
| Operating humidity | 5 to 95% noncondensing |
| Certifications | FCC, IC, CE |

Software

| | |
|-------------------------------|--|
| Modes | PtMP CPE, PtP* <small>*15.1 and later 15x series firmware.</small> |
| Services | SNMP, SSH, dynamic DNS, webserver, remote log, ping watchdog |
| Utilities | airView [®] , speed test, alignment, discovery, ping, traceroute, cable test, constellation |
| Auto distance adjustment | Yes |
| Auto power adjustment | Yes |
| Network | Bridge/Router* mode <small>*Router mode is available in PtMP CPE mode only.</small> |
| Security | Yes |
| Statcal reporting | Yes |
| Management interface | Bluetooth management for easy setup over UISP App WEB UI |
| Minimum software requirements | Any modern web browser iOS™ or Android™ based smartphone |



System

| | |
|-----------------------|---|
| Maximum throughput | 900+ Mbps* <small>*FW version 2.3.0 and later.</small> |
| Encryption | WPA2-PSK (AES) |
| Uplink/Downlink ratio | 25/75, 33/67, 50/50 |

RF

| | | | |
|----------------------|-----------|--------------------------------------|-----------------|
| Operating frequency* | US/CA | U-NII-1 | 5150 - 5250 MHz |
| | | U-NII-2A | 5250 - 5350 MHz |
| | | U-NII-2C | 5470 - 5725 MHz |
| | | U-NII-3 | 5725 - 5850 MHz |
| | EU | 2400 - 2483.5 MHz 5150 - 5875 MHz | |
| | Worldwide | 2400 - 2483.5 MHz 4800 - 6200 MHz | |

*Depends on regulatory region.

| | |
|-------------------------|--|
| Max. conducted TX power | 22 dBm (Per chain) |
| Management radio | 2400 - 2483.5 MHz |
| Channel bandwidth | 10/20/30/40/50/60/80/100 MHz* <small>*FW version 2.3.0 and later.</small> |
| Antenna gain | 13 dBi |
| Cross-pol isolation | 20 dB |
| Beamwidth | HPOL/VPOL/elevation: 45° |
| Polarization | Dual linear |

