

**DS-PWA64-Kit-WE(B)**  
**DS-PWA64-Kit-WE(B)(868MHz)**



- DS-PDMC-EG2-WE(B)\*1
- DS-PDP15P-EG2-WE(B)\*1
- DS-PKF1-WE(B)\*1
- DS-PWA64-L-WE(B)\*1

## ▪ Specification

| Software features                                  |                                                                                                                                                                          |
|----------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Area                                               | 16                                                                                                                                                                       |
| Zones                                              | 64 (up to 48 PIRCAMs)                                                                                                                                                    |
| Onboard video clips                                | 2+6(SD/NVR)                                                                                                                                                              |
| Installer                                          | 1                                                                                                                                                                        |
| User                                               | 30                                                                                                                                                                       |
| Admin                                              | 1                                                                                                                                                                        |
| Voice Prompt                                       | Supported                                                                                                                                                                |
| Loudspeaker built in                               | Supported                                                                                                                                                                |
| Memory Log stored                                  | 5000                                                                                                                                                                     |
| Programming tools                                  | Hik-Connect/Hik-ProConnect/Web Portal/IVMS4200/ Convergence Cloud                                                                                                        |
| Firmware upgrade                                   | APP/Web Portal                                                                                                                                                           |
| Arm modes                                          | Away/Stay                                                                                                                                                                |
| Automatic Arm/Disarm Timers                        | Supported                                                                                                                                                                |
| Forced Arming with Open Zones                      | Supported                                                                                                                                                                |
| Diagnostics via the APP or Web                     | Supported                                                                                                                                                                |
| ARC protocol                                       | SIA DC09 (SIA level 2, Contact ID), ISUP, ISAPI (SDK)<br>Hik-IP Receiver & Hik-IP Receiver Pro (Sur-Gard & Ademco 685)<br>Supports video verification and remote control |
| User APP for operating                             | Supported                                                                                                                                                                |
| Installer APP for programming                      | Supported                                                                                                                                                                |
| Web server for maintenance (offline configuration) | Supported                                                                                                                                                                |
| Hardware features                                  |                                                                                                                                                                          |
| GPRS on board                                      | Supported                                                                                                                                                                |
| Netowrk interface                                  | 1,100 Mbps/10 Mbps                                                                                                                                                       |
| Wi-Fi                                              | 2.4GHz                                                                                                                                                                   |
| SIM slot                                           | Single                                                                                                                                                                   |
| Tag reader built-in                                | NA                                                                                                                                                                       |
| Display                                            |                                                                                                                                                                          |
| LEDs Status                                        | Arm/Disarm, Alarm, Tamper, Fault, Cloud, Power                                                                                                                           |
| Electrical characteristics                         |                                                                                                                                                                          |
| Power supply                                       | Built in power supply                                                                                                                                                    |
| Battery type                                       | Built-in Li Battery                                                                                                                                                      |
| Battery life span                                  | Up to 12 hours at normal temperature (The battery working time can be significantly reduced at low temperatures)                                                         |
| Wireless transmission                              |                                                                                                                                                                          |
| RF frequency                                       | 868 Mhz                                                                                                                                                                  |
| Transmission Range(Free Space)                     | up to 2,000m                                                                                                                                                             |
| General                                            |                                                                                                                                                                          |
| Operation temperature                              | -10 °C to +55 °C ( please make sure the adapter is connected)                                                                                                            |
| Shell material                                     | Plastic                                                                                                                                                                  |
| Dimension(WxHxD)                                   | 170.0 mm (6.7") × 170.0 (6.7") mm × 38.6 mm (1.5")                                                                                                                       |
| Weight                                             | 557.5 g (19.7 oz)                                                                                                                                                        |
| Color                                              | White or Black                                                                                                                                                           |

| Device management |                                             |
|-------------------|---------------------------------------------|
| Keyfob            | 32                                          |
| Wireless sounder  | 4                                           |
| Tag reader        | 8 (Share with keypad)                       |
| Keypad            | 8 (Share with Tag Reader)                   |
| Wireless Repeater | 2                                           |
| Tag               | 32                                          |
| Multi Transmitter | 4                                           |
| Access control    | 16                                          |
| Energizer         | 8                                           |
| PIR Cam           | 48 (Share with RX Wireless Sounders, Smoke) |

# See Far, Go Further



[www.hikvision.com](http://www.hikvision.com)  
[support@hikvision.com](mailto:support@hikvision.com)

