

HD-TVI3.0 tester

1. Image



2. Product list

1. 12.6V charger(EU/US standard) x 1

2. BNC cable x 1

3. DC-DC cable x 1

4. Combined cable x 1

5. Adaptor x 2

6. User manual x 1

3. Key features

1. ABS+PC enclosure

2. 7" LCD screen, up to 800*480 resolution

3. 3-battery(2600MA) with 6A protective board

4. TVI3.0 mainboard

5. VGA/HDMI input, up to 1920*1080 resolution

4. Video input

1. TVI3.0 up to 720P@25/30/50/60fps and 1080P@25/30fps

2. Up the Coax function(HIKVISION-C protocol)

3. CVBS signal with PAL/NTSC/SECAM system

4. VGA video input

5. HDMI1.0

5. Power supply

1. Max.12.6V with 3-battery cascade

2. 11.1V-12.6V power supply for camera with DC-DC or USB

maximum 2A output

3. Special charger for 12.6V battery, input voltage is between 110V

voltage is 12.6V/1A. Optional US/ EU standard

6. Power Consumption

Max. 2.9W when TVI OFF

Max. 4.8W when TVI ON

7. Dimension

Tester only: 205MM*155MM*38MM

Tester with package: 28.5CM*18.5CM*7CM

Carton: 36.5CM*30CM*40CM(include 10 tester package)