

DS-D6022FL-B Indoor Wall-Mounted Digital Signage

The digital signage is used to broadcast information, release news, advertise products, etc., which is widely applicable to industry of entertainment, finance, traffic, etc.



Feature and Function


- **Metallic Appearance**
Light weight body with integrative design. The front high-transmittance tempered glass provides reliable protection.
- **Exquisite Image**
Industrial A+ panel, auto-coloring and image-enhancing engine.
- **Variable Materials**
Supports static and dynamic materials, including the pictures, audio, video, scrolling subtitle, PDF, webpages, live video, number calling, pop-up pictures, etc.
- **Flexible Program Schedule**
 - Supports free schedules and district play of multiple materials.
 - Supports variable play modes: play by day, play by week, play by loop, custom play, etc.
- **Centralized Management**
 - Remotely controls and manages one screen or more screens, such as timed startup/shutdown, quick startup/shutdown, brightness/volume timed adjustment, and screenshot preview.
 - Remotely releases programs and updates local (USB) programs.
- **Organization Permission**
 - 5-level organization is available for managing materials, programs, terminals, and users.
 - Supports creating custom users, allocating permission for users according to user level, and permission templates.
- **Multiple Security Safeguards**
 - 3-level check of materials, programs and schedules to prevent mistake release.
 - Encryption of data in storage and transmission to prevent data tampering.
 - With no default password, users can activate and set initial password to guarantee the password safety.



Specification

Model		DS-D6022FL-B
Display	Screen size	21.5 inch
	Active display area	476.06 (H) × 267.79 (V) mm (18.74 × 10.54 inch)
	Backlight	Direct illumination-type LED backlight
	Pixel pitch	0.24795(H) × 0.24795(V) mm (0.00976 × 0.00976 inch)
	Resolution	1920 × 1080@60 Hz
	Brightness	250 cd/m ²
	Viewing angle	Horizontal: 178°, vertical: 178°
	Color depth	8 bit
	Contrast ratio	1000:1
	Response time	14 ms
	Refresh rate	60 Hz
	Color gamut	72% NTSC
	Reliability	7 × 24 h
	Built-in system	Operation system
Processor		4-core Cortex-A17, main screen 1.8 GHz
Memory		2 GB
Built-in storage		8 GB EMMC, TF 32 GB, Max. 128 GB
Interface	Video & audio output	1 × AUDIO OUT
		2 × built-in speaker, 8 Ω 2 W
	Network interface	1 × LAN, Wi-Fi 2.4 G
General	Data transmission interface	2 × USB 2.0 interface, 1 × TF Card interface Note: The USB interface only supports for low power equipment, such as the keyboard or mouse.
	Material type	DAT, MPG, VOB, TS, AVI, MKV, MP4, MOV, 3GP, TS, FLV, WEBM, ASF, MP1, MP2, MP3, WMA, WAV, OGG, OGA, FLAC, ACC, M4A, XMF, MXMF, RTTTL, RTX, OTA, IMY, JPG, JPEG, BMP, GIF, PNG
	Power supply	100 to 240 VAC, 50/60 ± 3Hz
	Power consumption	≤ 40 W
	Standby consumption	≤ 10 W
	Working temperature	0 to 40 °C (32 °F to 104 °F)
	Working humidity	20% to 90% RH
	Storage temperature	-20 to 60 °C (-4 °F to 140 °F)
	Storage humidity	5% to 90% RH
	Product dimensions	533.26 (W) × 324.99 (H) × 44 (D) mm (without wall-mounted backboard) (20.99 × 12.79 × 1.73 inch)
		533.26 (W) × 324.99 (H) × 45 (D) mm (with wall-mounted backboard) (20.99 × 12.79 × 1.77 inch)
	Package dimensions	650 (W) × 475 (H) × 135 (D) mm (25.60 × 18.70 × 5.31 inch)
	Net weight	5.92 kg (13.05 lb.)
	Gross weight	7.38 kg (16.27 lb.)
Accessory	Power cord, Remote control, Battery, User manual, LOGO	

Physical Interface



No.	Interface	Description	No.	Interface	Description
1	SIM	SIM card slot	2	TF	TF card slot
3	AUDIO OUT	Audio output	4	AUDIO IN	Audio input
5	USB	USB 2.0 interface	6	USB	USB 2.0 interface
7	LAN	Network Interface	8	Switch	Power switch
9	100-240V~	Power interface	---	---	---


Accessory Device



Model	Material Code	Description	Picture
DS-D60S-B	302501440	Information release management server (integration of software and hardware)	

Available Model

DS-D6022FL-B


Dimension (unit: mm)





Without wall-mounted backboard

Typical Application



Distributed by



HIKVISION®

Headquarters

No.555 Qianmo Road, Binjiang District,
Hangzhou 310051, China
T +86-571-8807-5998
overseasbusiness@hikvision.com

Hikvision USA
T +1-909-895-0400
sales.usa@hikvision.com

Hikvision Australia
T +61-2-8599-4233
salesau@hikvision.com

Hikvision India
T +91-22-28469900
sales@pramahikvision.com

Hikvision Canada
T +1-866-200-6690
sales.canada@hikvision.com

Hikvision Thailand
T +662-275-9949
sales.thailand@hikvision.com

Hikvision Europe
T +31-23-5542770
sales.eu@hikvision.com

Hikvision Italy
T +39-0438-6902
info.it@hikvision.com

Hikvision Brazil
T +55 11 3318-0050
Latam.support@hikvision.com

Hikvision Turkey
T +90 (216)521 7070- 7074
sales.tr@hikvision.com

Hikvision Malaysia
T +601-7652-2413
sales.my@hikvision.com

Hikvision UK & Ireland
T +01628-902140
sales.uk@hikvision.com

Hikvision South Africa
Tel: +27 (10) 0351172
sale.africa@hikvision.com

Hikvision France
T +33(0)1-85-330-450
info.fr@hikvision.com

Hikvision Kazakhstan
T +7-727-9730667
nikia.panfilov@hikvision.ru

Hikvision Vietnam
T +84-974270888
sales.vt@hikvision.com

Hikvision UAE
T +971-4-4432090
salesme@hikvision.com

Hikvision Singapore
T +65-6684-4718
sg@hikvision.com

Hikvision Spain
T +34-91-737-16-55
info.es@hikvision.com

Hikvision Tashkent
T +99-87-1238-9438
uzb@hikvision.ru

Hikvision Hong Kong
T +852-2151-1761
info.hk@hikvision.com

Hikvision Russia
T +7-495-669-67-99
saleru@hikvision.com

Hikvision Korea
T +82-(0)31-731-8817
sales.korea@hikvision.com

Hikvision Poland
T +48-22-460-01-50
info.pl@hikvision.com

Hikvision Indonesia
T +62-21-2933759
Sales.Indonesia@hikvision.com

Hikvision Colombia
sales.colombia@hikvision.com