



PerformanceLine **IP65** **ONVIF**
2MP

KEY FEATURES

- WiFi compact IP camera with PIR of 10 m (90°) and IR illumination of 10 m for indoors
- H.265+/ H.265/ H.264+/ H.264/ MJPEG
- 1/2,8" CMOS, 2MP
- Dual Stream
- Mechanical filter
- 0,028 lux
- 2,8 mm lens (115,6°)
- OSD, 3D-DNR, BLC, HLC, WDR true 120 dB, ROI
- IVS
- Facial detection

HYU-630 HYU-630

WIFI COMPACT IP CAMERA WITH PIR OF 10 M (90°) AND IR ILLUMINATION OF 10 M FOR INDOORS

FEATURES

- 1/2,7" CMOS, 2 MP
- 1080P at 25 fps
- IR up to 10 meters
- Motion detection PIR up to 10 meters coverage
- H.265+/H.265/H.264+/H.264
- WDR true 120dB, BLC, HLC, 3DDNR, ROI
- MicroSD card slot up to 128GB (card is not included)
- PoE supported

SPECS

- 1/2,7" CMOS sensor, 2 MP
- Digital resolution: 1080P (1920x1080), 1,3MP (1280x960), 720P (1280x720)
- H.265+/H.265/H.264+/H.264/MJPEG
- Stream 1: 1080P, 1,3MP, 720P (25 fps)
- Stream 2: 640x480, 640x360, 320x240 (25 fps)
- Stream 3: 1080P, 720P, 640x360, 352x288 (25 fps)
- Day/night mode with removable mechanical filter
- PIR: 10 m, 90°x80°
- IR illumination: 10 meters
- Minimum illumination: 0,028 lux F2.0 color / 0 lux IR On
- 2,8 mm lens
- Viewing angle: 115,6°(H), 62°(V), 135°(D)
- White balance
- Automatic Gain Control
- Backlight compensation (BLC, HLC)
- WDR true 120 dB
- 3DDNR
- 1x ROI per stream
- Mirror mode
- Image adjustment: rotation, saturation, brightness, contrast, sharpness and white balance
- Intelligent functions: intrusion detection, line crossing detection
- Face detection
- 2 way audio (microphone and speaker incorporated)
- Reset button
- MicroSD/SDHC/SDXC card slot up to 128GB (card is not included)
- Network interface: RJ45 (10/100M)
- Network protocols: TCP/IP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, PPPoE, NTP,
- UPnP™, SMTP, SNMP, IGMP, QoS, IPv6
- WiFi 802.11b/g/n, 2,4 GHZ
- WiFi range up to 20 meters
- WiFi protocols: DQPSK, DBPSK, CCK (802.11b); OFDM/64QAM, 16-QAM, QPSK, BPSK
- Compatible with ONVIF (Profile S/G), ISAPI