



**H.265** **P2P** **ONVIF** **HDCVI™**  
**HDTVI** **AHD** **CVBS** **aisense**

# HYU-582 AI-ZVR5116M-4MLITE

16 CHANNEL 5 IN 1 ZVR HDCVI/HDTVI/AHD/CVBS + 24 IP CHANNELS

## KEY FEATURES

- 16 channel 5 in 1 ZVR HDCVI/HDTVI/AHD/CVBS + 24 IP channels
- H.265 Pro+, H265 Pro, H.265, H.264+, H.264
- 2 way audio
- Simultaneous playback of 8 channels
- Recording: 6MP (only IP), 4M-N, 3MP (channels 1, 2, 3 and 4, 15 fps, only TVI/AHD), 1080P (15 fps), 1080N, 720P, 960H, D1/4CIF, VGA, CIF, QVGA, QCIF (25 fps)
- HDMI and VGA simultaneous output at 1080P
- BNC output at D1/4CIF
- 1 HDD SATA
- RJ45 Gigabit
- Onvif, P2P, DDNS
- 2 USB, 1 RS485
- 12V DC



### Aisense series

- Aisense is able to differentiate, with great precision, a human body and a vehicle on a large number of objects. Not only can detect human and vehicle intrusion, it can also filter out false alarms that could have been triggered by moving objects that do not threaten.

### ESPECIFICACIONES

- 16 channel 5 in 1 ZVR H.265 Pro+/H265 Pro/H.265/H.264+/H.264
- 5 technologies: IP, HDCVI, HDTVI, AHD and CVBS
- H.265 Pro+ / H.265 Pro can be enabled to improve coding efficiency and reduce data storage costs
- 16 BNC inputs (coaxitron supported):
- HDCVI: 1080P / 720P
- HDTVI: 4MN / 3MP ( channels 1, 2, 3 and 4) / 1080P / 720P
- AHD: 4MN / 1080P/720P
- CVBS: 960H
- 24 IP inputs up to 6MP
- VGA and HDMI simultaneous output up to 1920x1080
- BNC video output
- 2 way audio: 1 RCA input / 1 RCA output
- Display resolution: 1080P, 1080N (960x1080), 720P, 960H, D1/4CIF, VGA, CIF
- Recording resolution: 6MP (only IP), 4M-N, 3MP (channels 1, 2, 3 and 4, TVI/AHD), 1080P, 1080N (960x1080), 720P, 960H, D1/4CIF, VGA, CIF

#### - Stream 1 on 4M-N/3MP mode:

- Stream at 4MN/3MP: 4M-N, 3MP (15 fps)

#### - Stream 1 on 1080P mode:

- Stream at 1080P: 1080P (15 fps), 720P, 960H, D1/4CIF, VGA, CIF (25/30 fps)
- Stream at 720P: 720P, 960H, D1/4CIF, VGA, CIF (25/30 fps)
- Stream 2: 960H, D1/4CIF (12 fps), CIF (25/30 fps)
- Simultaneous playback of 16 channels
- Maximum output bandwidth: 128 Mbps
- Internal capacity for 1 HDD SATA up to 10TB (not included)
- HDD quota mode supported; assign different capacities to different channels
- Graphic user interface (GUI) and one key start recording (Wizard)
- Video Content Analysis (VCA)
- Intelligent search for an efficient playback
- Third party cloud storage supported (Dropbox, Google Drive, Microsoft OneDrive)
- Supports 1 detection channel for sudden scene changes
- Network interface: Ethernet RJ45 (10/100/1000M) auto-adaptive
- Network protocols: TCP/IP, PPPoE, DHCP, P2P, DNS, DDNS, NTP, SADP, NFS, iSCSI, UPnP™, HTTPS
- Compatible with ONVIF
- Remote access up to 128 users
- Remote access via iPhone/iPad, Android
- Multi browser compatibility: Chrome, Firefox, Safari, IE

- P2P cloud, DDNS DEMES, Push and channel zero
- Connections: 2 USB 2.0, 1 RS485 half-duplex
- Power supply: 12V DC
- Consumption:  $\leq 25W$
- Working temperature:  $-10^{\circ}C \sim +55^{\circ}C$
- RH: 10~90%
- Dimensions: 315 x 242 x 45 mm (desktop)
- Weight:  $\leq 2$  kg