

# NK-1200

## Network Keyboard



Remote control of NVRs, network video

- transmitters, network video receivers and network cameras via the network connection

- Two-way audio communication

- Two-way audio communication

Convenient firmware upgrades via either the USB port or Ethernet

- Programmable by using the LCD screen

Firmware duplication and auto-recovery functions to enhance system stability

Management of multiple network keyboards via the network connection

### SPECIFICATIONS

| Communication         |  |
|-----------------------|--|
| Interface             | 2 x RS485(Terminal Block), 10/100/1000 Ethernet(RJ45, PoE IEEE802.3AF) |
| Baud Rate             | 300 bps ~ 115,200bps   |
| Supports protocols    | Over 70 sorts of PTZ protocol(IDIS, PANASONIC, PELCO, SAMSUNG, etc.)   |
| Supports Devices      | IP Camera, NVR, IDIS solution Suite                                    |
| Display               | LCD(2 Line)  |
| USB                   | 1x USB2.0, 1x USB3.0   |
| Audio in/out          | 1(3.5mm) / 1(3.5mm)  |
| configuration         | Joystick + Main Control Board  |
| S/W Upgrade           | USB, Network   |
| SETUP Program         | IDIS Discovery   |
| General               |  |
| Dimension(W x H x D)  | 376.9mm x 95mm x 177.6mm (15.0" x 3.7" x 7.0")                         |
| Unit Weight(Kg)       | 1.1kg (2.43lb)   |
| Operating Temperature | 0°C ~ 40°C (32°F ~ 104°F)  |
| Power Input           | DC 48V, 1A, PoE(IEEE 802.3af class 0)                                  |
| Approvals             | FCC, CE, KC  |



### PRODUCT IMAGE



### DIMENSIONS