

4 Bay eSATA Storage

DA-ES1104

(compatible to H.264 NVR)

DA-ES1104B

(compatible to H.265 NVR)

DA-ES1104C

(compatible to IR-100, IR-300 only)

DA-ES1104D

(compatible to IR-300A with 10Tera HDD)



- 19" Rack Mount Type
- Best Combination with DirectIP™ NVR
- Supports RAID Levels 0, 1 + 0, 5
- SATA-to-SATA Port Multiplier
- Maximum of 3.0Gbps Transfer Rate (SATA II)
- Installation of the Maximum of Four Hard Disk Drives
- Maximized Space Saving and Capacity Relative to Cost
- Easy Expansibility to a Very Large Storage Pool

SPECIFICATIONS

HARDWARE	
Interface	eSATA x 1
Number of Drives	SATA II x 4
Drive Size	3.5"
Drive Type	SATA II
Supported Device	DA-ES1104 DR-22xx, DR-41xx, DR-42xx, DR-61xx, DR-62xx NVR, DR-8364(F)(R) NVR*, HD-TVI DVR
	DA-ES1104B DR-23xx, DR-43xx, DR-63xx NVR, DR-24xx NVR, DR-8416/8432(D)
	DA-ES1104C Compatible Recorder : IR-100, IR-300, DR-8364(F)(R) v5.4.1 or higher
	DA-ES1104D Compatible Recorder : IR-300A
PERFORMANCE	
Type and Rate	SATA II (3Gbps)
RAID	0, 1 + 0, 5
Max Drive Capacity	DA-ES1104 24TB (up to 6TB per bay)
	DA-ES1104B 16TB (up to 4TB per bay)
	DA-ES1104C 40TB (up to 10TB per bay)
	DA-ES1104D 40TB (up to 10TB per bay)
GENERAL	
Dimensions (W x H x D)	480mm x 44mm x 346mm (18.9" x 1.7" x 13.6")
Weight	6.4kg (14.11lb)
Operation Temperature	0°C ~ 45°C (32°F ~ 113°F)
Power Input	100V ~ 240VAC, 0.6-0.3A, 50/60Hz
Power Consumption	100-240V~, 50/60Hz, 0.6-0.3A, 40W
Approvals	FCC, CE

* DR-8364(F)(R) is compatible with DA-ES1104 when the storage mode of DA-ES1104 is set to RAID 1+0 or RAID 5. Please don't use the RAID 1 or No-RAID mode on DA-ES1104 for compatibility with DR-8364(F)(R) at this time.

DIMENSIONS

(Unit - mm)

