



KEY FEATURES

- WiFi vandal IP dome with IR of 10 m, for outdoors, 4MP
- H.264/H.264+/MJPEG
- 1/3" CMOS, 4MP
- Dual Stream
- MEchanical filter
- 0,01 lux
- 2,8 mm fixed lens (106°)
- OSD, 3D-NR, BLC, real WDR 120dB, ROI
- IVS
- MicroSD//SDHC/SDXC

RELATED PRODUCTS



HYU-394 HYU-394

WIFI VANDAL IP DOME WITH IR OF 10 M, FOR OUTDOORS, 4MP

- 1/3" CMOS, 4 MP- Digital resolution: 4MP (2688x1520), 1080P (1920x1080), 720P (1280x720), etc.- H.264/H.264+/MJPEG- Stream 1: 4MP (20 fps), 1080P, 720P (25 fps)- Stream 2: D1/4CIF, CIF (25 fps)- Day/night mode with removable mechanical filter- IR illumination: 10 meters- Minimum illumination: 0,01 lux F1.2 color / 0 lux IR On- 2,8 mm fixed lens (106°)- Backlight compensation- Real WDR 120dB- 3D noise reduction- Mirror mode- ROI- Privacy mask- Intelligent functions: intrusion detection, tripwire, motion detection, dynamic analysis- MicroSD/SDHC/SDXC up to 128GB (card is not included)- Network interface: RJ45 (10/100 Base-T)- WiFi 802.11b/g/n incorporated- WiFi range: up to 15 meters- Netowrk protocols: TCP/IP, UDP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, PPPoE, NTP, UPnP, SMTP, SNMP, IGMP, 802.1X, QoS, IPv6, Bonjour- Compatible with ONVIF (profile S, profile G), PSIA, CGI, ISAPI- Compatible with DDNS DEMES- IP67- IK08- Power supply: 12V DC, max 5W- PoE 802.3af supported- Working temperature: -30°C ~ +60°C- HR: <95%, without condensation- Metal case- Dimensions: 99,3 x 96,7 x 52,8 mm- Weight: 600 g- Power supply is not included