

Avatar



Niveles programables

Programmable levels
Niveaux programmables
Níveis programáveis

Ver anexos regulación pag. 364

See annexes regulation pag. 364
Voir règlement annexe pag. 364
Ver anexo regulação pag. 364

Luminaria CMR

Luminaire CMR
Luminaire CMR
Luminária CMR



Core Manager Ready

S Soluciones

Solutions
Des solutions
Soluções



SAFELIGHT



	W _{LED}	W _{LUM.}		Φ LED (Tj 25°C)	Φ LED	Φ LUM.	Φ/W	η	
474412	12W	16W	350mA	2.260lm	2.241lm	1.927lm	121 lm/W	86%	12
474429	18W	22W	500mA	3.112lm	2.977lm	2.560lm	116 lm/W	86%	12
474436	24W	30W	700mA	4.173lm	3.938lm	3.387lm	113lm/W	86%	12
474443	36W	42W	1000mA	5.481lm	5.216lm	4.478lm	106lm/W	86%	12
533416	30W	36W	500mA	5.015lm	4.813lm	3.982lm	111lm/W	83%	20
533058	40W	48W	700mA	6.723lm	6.351lm	5.270lm	110lm/W	83%	20
533768	60W	66W	1000mA	9.058lm	8.557lm	7.094lm	107lm/W	83%	20
537896	36W	41W	500mA	6.018lm	5.733lm	4.755lm	116lm/W	83%	24
532631	48W	55W	700mA	8.168lm	7.568lm	6.281lm	114lm/W	83%	24
533393	72W	76W	1000mA	10.966lm	10.357lm	8.622lm	113lm/W	83%	24

Bajo pedido/On request/Sur commande/A pedido



K				
3.000K	DALI	PPD	CII	PC (IK10)
5.000K	DN	PPI		
PC Ambar (I≤700mA)	DN LM			

Accesorios/Accessories/Accessoires/Acessórios

+ INFO PAG. 98

534222

Kit adaptador a poste 50mm
Post adapter kit 50mm
Kit adaptateur pole 50mm
Kit de adaptador de poste 50mm

538282

Kit adaptador a poste 42mm
Post adapter kit 42mm
Kit adaptateur pole 42mm
Kit de adaptador de poste 42mm

220-240V

50-60Hz

CI

IP66

IK08

L70 B10>100.000h
(500<I≤1.000mA)
L90 B10>100.000h (I≤500mA)

-30°C~+35°C

VA

>70

4.000K

5N

0.0%

RAL 9007

VT


AL iap

Max. 5kg

0,151m²

Overstorm

SYSTEM SHIELD



[GRÁFICOS: Unidades en mm/ GRÁFICS: Units in mm/ GRÁFIQUES: Unités en mm/ GRÁFICOS: Unidades em mm]