



PerformanceLine **P2P** **ONVIF**

KEY FEATURES

- Wi-Fi IP compact camera with PIR of 8 m (90°) and IR illumination of 10 m, for indoors
- H.264/H.264+/MJPEG
- 1/2,8" CMOS, 2MP
- Dual stream
- Mechanical filter
- 0,01 lux
- 2,8 mm fixed lens
- OSD, 3D-NR, BLC, real WDR 120 dB, ROI
- IVS
- Microphone and speaker incorporated

HYU-420 HYU-420

WIFI IP COMPACT CAMERA WITH PIR OF 8 M (90°) AND IR ILLUMINATION OF 10 M, FOR INDOORS

- 1/2,7" CMOS, 2 MP
- 1080P (1920x1080), 1,3MP (1280x960), 720P (1280x720)
- H.264/H.264+/MJPEG
- Stream 1: 1080P, 1,3MP, 720P (25 fps)
- Stream 2: 640x360, 352x288 (25 fps)
- Day/night mode with removable mechanical filter
- PIR: 8 m, 90°
- IR illumination: 10 meters
- Minimum illumination: 0,01 lux F1.2 color / 0 lux IR On
- 2,8 mm fixed lens (115,6°)
- BACklight compensation
- Real WDR 120 dB
- 3D digital noise reduction
- ROI
- Mirror mode
- Image adjustment: brightness, saturation, contrast, and image rotation
- IVS: intrusion detection, tripwire, motion detection, dynamic analysis
- Facial detection
- 2 way audio (microphone and speaker incorporated)
- Alarm: 1 in / 1 out
- MicroSD/SDHC/SDXC up to 128GB (card is not included)
- Network interface: RJ45 (10/100 Base-T)
- Wi-Fi incorporated 802.11b/g/n
- Wi-Fi up to 15 meters
- Network protocols: TCP/IP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, PPPoE, NTP, UPnP, SMTP, SNMP, IGMP, 802.1X, QoS, IPv6
- Compatible with ONVIF (Profile S/G), ISAPI
- Compatible with DDNS DEMES
- Power supply: 12V DC, max 5W
- PoE supported 802.3af
- Working temperature: -10°C ~ +40°C
- RH: <95%, without condensation
- 100% PVC case
- Dimensions: 72,3 x 89,9 x 131,3 mm
- Weight: 400 g