

KPC138E

21 LEDs IR Camera



● FEATURES

- (1) High sensitivity in the dark environment, 0.1 Lux / F2.0, 0Lux (IR ON)
- (2) Day and night features for 24-hour surveillance
- (3) Excellent image quality
- (4) IR LED effective range reaches up to 15 meters
- (5) IP67 standard approved case

● SPECIFICATIONS*

| MODEL | KPC138E |
|----------------------------|--|
| Pick-up Element | 1/3" H.R. Color CCD image sensor |
| Number of Pixels | 771(H) x 492(V) <NTSC> / 753(H) x 582(V) <PAL> |
| Resolution | 520 TV Lines |
| Min. Illumination | 0.1 Lux / F2.0, 0Lux (IR ON) |
| IR LED | 21 units |
| Effective Range | Up to 15 Meters |
| S/N Ratio | More than 48dB (AGC OFF) |
| Electronic Shutter | 1/60 (1/50) to 1/100,000 sec. |
| Lens | f3.6mm / F2.0 |
| Lens Angle | 92.6° |
| IRIS Mode | AES |
| White Balance | ATW |
| Video Output | 1.0 Vp-p composite, 75Ω |
| Power Source (±10%) | DC12V |
| Current Consumption (±10%) | 70mA (IR OFF), 270mA (IR ON) |
| Dimensions (mm)** | 140.19(L) x 55.2(W) x 79.58(H) |
| IP Rating | IP67 |

* The specifications are subject to change without notice.

** Dimensional Tolerance: ± 5mm

Good Sensitivity in Low Illumination

KPC13x Series



Conventional



True Color

KPC13x Series



Conventional

