

NUUO Crystal™

SECURE • POWERFUL • OPEN

Powered by Titan




Scalable Solution

Leading Edge Technology


Seamless Integration



System Structure



Product Overview



Industry Applications

Retail



- View & Evaluate day-to-day operations

Industrial



- Process Monitoring
- Mitigate Worker Accident Risks

Healthcare



• Patient and Staff Safety • Reduce Narcotics Loss

Education



 Campus Safety and Security • Deter Property Loss

Entertainment



- Visitor and staff's safety
- Reduce frivolous litigation claims

Logistic



- Reduce cargo theft and damage

Product Matrix

Product	NUUO Crystal™ Ultimate	NUUO Crystal™ Enterprise	NUUO Crystal™ Professional	NUUO Titan NVR
Max. Camera Channels per Recording Server	64	64	64	64
Number of Stream Out per Recording Server	256	256	256	128
Recording Throughput	Up to 550Mpbs	Up to 550Mpbs	Up to 550Mpbs	Up to 250Mpbs
Recording Server Failover	•			
Video Wall	+	+		
System Navigator	+	+	+	+
Diagnostics Service	+	+	+	*
NUUO Fisheye Dewarp	+	+	+	+
Central Management	+	+	+	*
Individual Retention Condition	+	+	+	
Boost Recording	+	+	*	
Multi Stream Setting	+	+	+	
SDK Support	*	*	*	*
3rd Party Support (POS/ Access Control/ LPR)	+	+	*	
Client Support	Windows/Mac	Windows/Mac	Windows/Mac	Windows/Mac

NUUO Crystal™ Ultimate, Enterprise, and Professional licenses are not compatible with each other. Only 1 type of license may be installed onto a single management server.





www.nuuo.com

Specification

Product Image			0					
Туре	To	wer	Rack-m	ount 1U	Rack-mount 2U Rack-mount 2U (Redund			(Redundant Power)
Model Name	CT-4000	NT-4040	CT-4000R	NT-4040R	CT-8000R	NT-8040R	CT-8000RP NT-8040F	
Recording Throughput	250 Mbps (MAX), 150 Mbps (OPTIMAL)			CT-8000 Series: 250 Mbps(1 Volume Group) 400 Mbps (2 Volume Group) 550 Mbps (3 Volume Group) NT-8000 Series: 250 Mbps				
Number of Live View	CT-4000 S	CT-4000 Series: 4CH per View, View tour to 64CH			40011 14 14 1 1 1 1 1 1 1			
Spot-out(Local display)	NT-4000 Series: 1CH per View, View tour to 64CH			16CH per View, View tour to 64CH				
CPU Model	Intel Atom			Intel Core i5				
Number of Drives	4xSATA II			8xSATA II				
Max Storage Per Drive*1		6TB			6TB			
Max Internal Total Storage	24TB			48TB				
RAID Level	RAID 0, 1, 5, 10							
I/O Interface	6 x USB 2.0 4 x USB 2.0			2 x USB3.0;				
	(for mou	(for mouse, UPS); (for mouse, UPS);			2 x USB2.0;			
	1 x eSATA	A (for DAS)	1 x eSATA	A (for DAS)	1 x eSATA (for DAS)			
LAN	2 x Gigabit Port, RJ45							
LAN Transmission Speed	10/100/1000 Mbps							
Voltage	100-240V							
Power Consumption	Full loading:50W		Full loadir	ng: 150W	Full loadi	ng: 160W		
	Max: 250W			Max:	500W	Max: 500W (Re	dundant Power)	
Dimension (HxWxD)	212 x 200	x 318 mm	45 x 447	x 429 mm	88 x 447 x	c 583 mm	88 x 447	x 583 mm
Weight (Without Drive)	5.3 kg (11.7 lbs)	6.0 kg (13.2 lbs)	11.4 kg (25.1 lbs)	13.2 kg	(29.1 lbs)
Temperature	Operating: 0°C-40°C							
Humidity	Operating: 5%-95%							
Supported Languages (17 languages)	Czech, Chinese(Simplified), Chinese(Traditional), English, Finnish, French, Germany, Italian, Japanese, Korean, Polish, Portuguese (Brazil), Russian, Spanish, Swedish, Thai, Turkish							

^{*1} Refer NUUO web site for hard drive compatibility list (http://www.nuuo.com/SupportCamera.php?node_id=12#)

License Type

License	Part Name	License		Part Name
Ultimate	CT-CAM-ULT CV-CAM-ULT'3	Point of Sale		CT-POS-Generic
Enterprise	CT-CAM-ENT CV-CAM-ENT*2*3	Access Control	R	CT-ACC-Generic
Professional ²	CT-CAM-PRO	Upgrade (Enterprise → Ultimate)		CT-CAM-UPU CV-CAM-UPU '2 '3
Titan Expansion	NT-TITAN-UP	Upgrade ^{·²} (Professional → Enterprise)		CT-CAM-UPE

^{*2} Not available in North America
*3 Pure NUUO Crystal™ Software on VMware vSephere

